Mazinoor
Different Experience Beyond Illumination

UECONELED840W-BL

About Product

Decorative Beacon, 4000K, 3W, Opal white



Technical Information

Luminaire Name:	Decorative Beacon
accessory Name:	Decorative Beacon
Catalog Code/product code:	UECONELED840W-BL
Mounting Type:	Vertical pole mounting
Application:	Street and Urban lighting
Light source type:	DOB LED (PF> 0.5)
Module/ Lamp quantity:	1
CCT (Color temperature):	4000K - Neutral White
Light source:	LED
Lumen maintenance:	> 50.000 hours
Lumen maintenance factor:	L70
CRI (Color rendering index):	> 80
Power Consumption:	3
IP (Ingress Protection):	IP65
Insulation Class:	Class I
Max. Ambient Temperature:	+55°C
Min. Ambient Temperature:	-40°C
Mains voltage:	220~240 VAC
Voltage Frequency:	50 Hz
Wire / Cable Spec:	PVC flexible wire
Wire cross section:	0.5
Terminal material:	Polyamide
Terminal Spec:	3-Pole (Size: 2.5)
Body Material:	Cast aluminum with high pressure die-cast aluminum ring
Body Coating:	Powder coated

© Mazinoor reserves all rights to make changes and improving modifications to product configurations without prior notice.
The most up to date data are shown on this website and supercedes any relevant data on prior publications.

Mazinoor
Different Experience Beyond Illumination

UECONELED840W-BL

Body Color:	Black
RAL:	RAL9005
Diffuser/Glass Material:	Polycarbonate
Diffuser/Glass Characteristic:	UV stabilized
Lens Material:	Clear polycarbonate
Gasket Material:	silicon
Gasket Characteristic:	High thermal resistance، Resistant to pressure
Interior Connection Material:	Galvanized coated
Exterior Connection Material:	Dacromet coated
Packaging type:	Nylon cover and carton
Other Characteristics:	Opal white diffuser Uniform luminance of diffuser with clear polycarbonate lens
Weight(Kg):	0.7
Dimensions(mm):	Ø118x560

© Mazinoor reserves all rights to make changes and improving modifications to product configurations without prior notice.
The most up to date data are shown on this website and supercedes any relevant data on prior publications.