

UECONELED840R-BL

About Product

Decorative Beacon, 4000K, 3W, Clear red



Technical Information

| Luminaire Name: | Decorative Beacon |
|------------------------------|---|
| accessory Name: | Decorative Beacon |
| Catalog Code/product code: | UECONELED840R-BL |
| Mounting Type: | Vertical pole mounting |
| Application: | Street and Urban lighting |
| Light source type: | DOB LED (PF> 0.5) |
| Module/ Lamp quantity: | 1 |
| CCT (Color temperature): | 4000K - Neutral White |
| Light source: | LED |
| Lumen maintenance: | > 100.000 hours |
| Lumen maintenance factor: | L80 |
| CRI (Color rendering index): | > 80 |
| Power Consumption: | 3 |
| IP (Ingress Protection): | IP65 |
| Insulation Class: | Class I |
| Max. Ambient Temperature: | +55°C |
| Min. Ambient Temperature: | -30°C |
| Mains voltage: | 220~240 VAC |
| Voltage Frequency: | 50 Hz |
| Wire / Cable Spec: | PVC flexible wire |
| Wire cross section: | 0.5 |
| Terminal material: | Polyamide |
| Terminal Spec: | 3-Pole (Size: 2.5) |
| Body Material: | Cast aluminum with high pressure die-cast aluminum ring |
| Body Coating: | Powder coated |



UECONELED840R-BL

| Body Color: | Black |
|--------------------------------|---|
| RAL: | RAL9005 |
| Diffuser/Glass Material: | Polycarbonate |
| Diffuser/Glass Characteristic: | UV stabilized |
| Lens Material: | Clear polycarbonate |
| Gasket Material: | silicon |
| Gasket Characteristic: | High thermal resistance. Resistant to pressure |
| Interior Connection Material: | Galvanized coated |
| Exterior Connection Material: | Dacromet coated |
| Packaging type: | Nylon cover and carton |
| Other Characteristics: | Clear diffuser in red Uniform luminance of diffuser with clear polycarbonate lens |
| Weight(Kg): | 0.7 |
| Dimensions(mm): | Ø118x560 |