

$2x36\ W\ T8\ explosion\ proof\ fluorescent\ luminaire,\ Through\ Wiring,\ Zone\ 1/21,\ Class\ II\ 2\ G\ EX\ d\ e\ q\ IIC\ T4\ Gb$

About Product




Technical Information



$2x36\ W\ T8\ explosion\ proof\ fluorescent\ luminaire,\ Through\ Wiring,\ Zone\ 1/21,\ Class\ II\ 2\ G\ EX\ d\ e\ q\ IIC\ T4\ Gb$

Photometric Graph



Ceiling		70	70	50	50	30	70	70	50	50	30
Walls		50	30	50	30	30	50	30	50	30	30
ρ Floor		20	20	20	20	20	20	20	20	20	20
Room Size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	14.7	16.0	15.2	16.5	17.0	11.9	13.2	12.4	13.7	14.2
	3H	17.6	18.8	18.1	19.3	19.8	13.0	14.2	13.5	14.7	15.2
	4H	18.9	20.0	19.4	20.5	21.1	13.3	14.4	13.8	14.9	15.5
	6H	20.0	21.1	20.5	21.6	22.2	13.5	14.5	14.0	15.0	15.6
	8H	20.5	21.5	21.1	22.1	22.7	13.5	14.5	14.0	15.0	15.6
	12H	21.0	22.0	21.6	22.5	23.1	13.5	14.5	14.0	15.0	15.6
4H	2H	15.1	16.2	15.6	16.7	17.3	13.1	14.2	13.6	14.7	15.3
	3H	18.3	19.3	18.9	19.9	20.5	14.6	15.6	15.2	16.1	16.8
	4H	19.8	20.7	20.4	21.3	21.9	15.1	16.0	15.7	16.6	17.2
	6H	21.1	21.9	21.7	22.5	23.2	15.4	16.2	16.0	16.8	17.5
	8H	21.8	22.5	22.4	23.1	23.8	15.5	16.2	16.1	16.8	17.5
	12H	22.4	23.1	23.0	23.7	24.4	15.5	16.2	16.1	16.8	17.5
8H	4H	20.1	20.8	20.7	21.4	22.1	16.4	17.2	17.0	17.8	18.5
	6H	21.7	22.3	22.3	22.9	23.6	17.1	17.7	17.8	18.4	19.1
	8H	22.4	23.0	23.1	23.7	24.4	17.3	17.9	18.0	18.6	19.3
	12H	23.3	23.7	23.9	24.4	25.2	17.5	18.0	18.1	18.6	19.4
12H	4H	20.1	20.8	20.7	21.4	22.1	16.7	17.4	17.4	18.0	18.7
	6H	21.7	22.3	22.4	22.9	23.7	17.6	18.2	18.3	18.9	19.6
	8H	22.6	23.1	23.3	23.8	24.5	18.0	18.5	18.7	19.2	20.0
Variation of t	he observer	position t	for the lum	inaire dist	ances S						
S = 1.0H		+0.1 / -0.1					+0.1 / -0.1				
S = 1.5H		+0.2 / -0.2				+0.2 / -0.3					
S = 2.0H		+0.2 / -0.3					+0.4 / -0.7				
Standard table		BK11					BK13				
Correction Summand		0.8					-4.5				

Dimensional Drawing

