


ELEGANT 4x24W T5 recessed fluorescent luminaire, Specular pre-anodized aluminium double optic parabolic louver (MIRO®) with electronic ballast

About Product




Technical Information



ELEGANT 4x24W T5 recessed fluorescent luminaire, Specular pre-anodized aluminium double optic parabolic louver (MIRO®) with electronic ballast

Photometric Graph



Ceiling		70	70	50	50	30	70	70	50	50	30
Walls		50	30	50	30	30	50	30	50	30	30
o Floor		20	20	20	20	20	20	20	20	20	20
Room Size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	5.5	6.5	5.8	6.7	6.9	20.7	21.6	20.9	21.9	22.
	3H	5.4	6.2	5.7	6.5	6.7	20.5	21.4	20.9	21.7	21.
	4H	5.3	6.1	5.6	6.4	6.6	20.5	21.3	20.8	21.6	21.
	6H	5.2	6.0	5.6	6.3	6.5	20.4	21.2	20.7	21.4	21.
	8H	5.2	5.9	5.5	6.2	6.5	20.4	21.1	20.7	21.4	21.
	12H	5.1	5.8	5.5	6.1	6.5	20.3	21.0	20.7	21.3	21.
4H	2H	5.9	6.8	6.3	7.0	7.3	20.4	21.3	20.8	21.5	21.
	3H	5.8	6.5	6.2	6.8	7.1	20.3	21.0	20.7	21.3	21.
	4H	5.8	6.3	6.1	6.7	7.0	20.3	20.9	20.7	21.2	21.
	6H	5.7	6.2	6.1	6.6	6.9	20.2	20.7	20.6	21.1	21.
	8H	5.6	6.1	6.1	6.5	6.9	20.2	20.6	20.6	21.0	21.
	12H	5.6	6.0	6.0	6.4	6.8	20.1	20.5	20.6	20.9	21.
SH	4H	5.7	6.1	6.1	6.5	6.9	20.2	20.6	20.6	21.0	21.
	6H	5.6	5.9	6.0	6.4	6.8	20.1	20.4	20.5	20.9	21.
	8H	5.5	5.9	6.0	6.3	6.8	20.0	20.4	20.5	20.8	21.
	12H	5.5	5.8	6.0	6.2	6.7	20.0	20.3	20.5	20.7	21.
12H	4H	5.6	6.0	6.1	6.4	6.9	20.1	20.5	20.6	20.9	21.
	6H	5.5	5.9	6.0	6.3	6.8	20.0	20.4	20.5	20.8	21.
	8H	5.5	5.8	6.0	6.2	6.7	20.0	20.3	20.5	20.7	21.
/ariation of	the observer	position I	for the lum	inaire dist	ances S						
S = 1.0H		+2.3 / -9.7					+1.1 / -1.6				
S = 1.5H		+3.7 / -19.1				+2.1 / -5.2					
S = 2.0H		+5.4 / -26.5				+3.9 / -14.0					
Standard table		BK00					BK00				
Correction		-6.6					-3.6				
Summ	and			-0.0					-3.0		

Dimensional Drawing

