

**DIANA LED IP54 recessed Downlight, Satin white Polystyrene diffuser, 15cm Dia., 6500K, LED4, 2200 Lumens, 19W**

**About Product**

---




**Technical Information**

---

DIANA LED IP54 recessed Downlight, Satin white Polystyrene diffuser, 15cm Dia., 6500K, LED4, 2200 Lumens, 19W

Photometric Graph



Glare Evaluation According to UGR												
ρ Ceiling		70	70	50	50	30	70	70	50	50	30	
ρ Walls		50	30	50	30	30	50	30	50	30	30	
ρ Floor		20	20	20	20	20	20	20	20	20	20	
Room Size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis					
2H	2H	20.7	21.9	21.0	22.1	22.4	20.7	21.9	21.0	22.1	22.4	
	3H	21.9	23.0	22.3	23.3	23.6	21.9	23.0	22.3	23.3	23.6	
	4H	22.3	23.4	22.7	23.6	23.9	22.3	23.4	22.7	23.6	23.9	
	6H	22.6	23.5	22.9	23.8	24.1	22.6	23.5	22.9	23.8	24.1	
	8H	22.6	23.5	23.0	23.8	24.2	22.6	23.5	23.0	23.8	24.2	
4H	12H	22.6	23.5	23.0	23.8	24.1	22.6	23.5	23.0	23.8	24.1	
	2H	21.1	22.1	21.4	22.4	22.7	21.1	22.1	21.4	22.4	22.7	
	3H	22.5	23.4	22.9	23.7	24.1	22.5	23.4	22.9	23.7	24.1	
	4H	23.0	23.8	23.4	24.2	24.5	23.0	23.8	23.4	24.2	24.5	
	6H	23.4	24.0	23.8	24.4	24.8	23.4	24.0	23.8	24.4	24.8	
8H	8H	23.5	24.1	23.9	24.5	24.9	23.5	24.1	23.9	24.5	24.9	
	12H	23.5	24.1	23.9	24.5	24.9	23.5	24.1	23.9	24.5	24.9	
	2H	21.1	22.1	21.4	22.4	22.7	21.1	22.1	21.4	22.4	22.7	
12H	4H	23.2	23.8	23.6	24.2	24.6	23.2	23.8	23.6	24.2	24.6	
	6H	23.6	24.1	24.1	24.6	25.0	23.6	24.1	24.1	24.6	25.0	
	8H	23.8	24.2	24.2	24.7	25.1	23.8	24.2	24.2	24.7	25.1	
	12H	23.8	24.2	24.3	24.7	25.2	23.8	24.2	24.3	24.7	25.2	
	4H	23.2	23.8	23.7	24.2	24.6	23.2	23.8	23.7	24.2	24.6	
12H	6H	23.7	24.1	24.1	24.5	25.0	23.7	24.1	24.1	24.5	25.0	
	8H	23.8	24.2	24.3	24.6	25.1	23.8	24.2	24.3	24.6	25.1	
	12H	23.8	24.2	24.3	24.6	25.1	23.8	24.2	24.3	24.6	25.1	
Variation of the observer position for the luminance distances S												
S = 1.0H		+0.2 / -0.3					+0.2 / -0.3					
S = 1.5H		+0.4 / -0.8					+0.4 / -0.8					
S = 2.0H		+0.9 / -1.4					+0.9 / -1.4					
Standard table		BK04					BK04					
Correction Summand		4.0					4.0					
Corrected Glare Indices referring to 2200lm Total Luminous Flux												

Dimensional Drawing

