


## M217LEDPV-W

### LEADER office exit light, Arrow right/left sign, 4000K, 9W, White



#### About Product

LEADER modern emergency/exit light is designed and manufactured by Mazinoor for emergency and exit light in offices and commercial buildings. Sturdy structure and high lighting efficacy are among the highlights of this luminaire.



#### Technical Information

Luminaire Name:	LEADER
Catalog Code/product code:	M217LEDPV-W
Mounting Type:	Surface Mounted, Wall mounting with bracket, Recessed-Gypsum false ceiling
Application:	Shopping centers, Office, Hospitality, Gallery and museum, Hypermarket, Emergency
Light source type:	LED
Module/ Lamp quantity:	1
CCT (Color temperature):	4000K - Neutral White
Light source:	LED
Lumen maintenance factor:	L85
CRI (Color rendering index):	> 80
Power Consumption:	9
Luminous Flux:	-
IP (Ingress Protection):	IP40
Insulation Class:	Class I
Ballast/ Driver:	Constant Current Driver
FLICKER:	Flicker Free
Ballast/ driver Spec:	Non-dimmable
Ballast/ Driver (Channel quantity):	Single channel
Mains voltage:	220~240 VAC±10%, 198~264 VDC
Voltage Frequency:	50/60 Hz ; 0 (DC)

## M217LEDPV-W

### LEADER office exit light, Arrow right/left sign, 4000K, 9W, White

Wire / Cable Spec:	PVC solid wire
Wire cross section:	0.5
Socket & Plug:	Polyamide
Socket & Plug Spec:	3-Pole (Size: 2.5)
Body Material:	Extruded aluminum profile
Body Coating:	Powder coated
Body Color:	White
RAL:	RAL9003
End Caps Material:	Die-Cast aluminum
Light Distribution:	-
Clamp Material:	Galvanized steel sheet
Packaging type:	Nylon cover and carton
Other Characteristics:	Clear Acrylic sign board
Weight(Kg):	1.15
Dimensions(mm):	340x45x215
Luminaire mechanical impact resistance:	-
Other/Spare parts:	5x40 screws (2 pcs.), Wall plugs

## M217LEDPV-W

**LEADER office exit light, Arrow right/left sign, 4000K, 9W, White**

### Photometric Graph

---

### Dimensional Drawing

---

