

ELENA ViVo adjustable recessed downlight, Medium light distribution, 15-cm Dia., 3000K, LED3, 3200 Lumens, 36W, Black

About Product

ELENA adjustable recessed downlight is Mazinoor state of the art design suitable for modern retail shop and commercial lighting applications. Adjustable light direction, directed light distribution, energy saving, and aesthetically beautiful design are among the highlights of this luminaire.




Technical Information



ELENA ViVo adjustable recessed downlight, Medium light distribution, 15-cm Dia., 3000K, LED3, 3200 Lumens, 36W, Black

Photometric Graph



Ceiling		70	70	50	50	30	70	70	50	50	30
Walls		50	30	50	30	30	50	30	50	30	30
Floor		20	20	20	20	20	20	20	20	20	20
Room Size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	3.3	4.0	3.6	4.2	4.4	3.3	4.0	3.6	4.2	4.4
	3H	4.1	4.7	4.4	4.9	5.2	4.1	4.7	4.4	4.9	5.2
	4H	4.3	4.9	4.6	5.1	5.4	4.3	4.9	4.6	5.1	5.4
	6H	4.6	5.1	4.9	5.4	5.7	4.6	5.1	4.9	5.4	5.7
	8H	4.7	5.1	5.0	5.4	5.7	4.7	5.1	5.0	5.4	5.7
	12H	4.7	5.2	5.0	5.5	5.8	4.7	5.2	5.0	5.5	5.8
4H	2H	3.5	4.0	3.8	4.3	4.6	3.5	4.0	3.8	4.3	4.6
	3H	4.5	4.9	4.8	5.2	5.5	4.5	4.9	4.8	5.2	5.5
	4H	4.7	5.1	5.1	5.5	5.8	4.7	5.1	5.1	5.5	5.8
	6H	5.1	5.5	5.5	5.8	6.2	5.1	5.5	5.5	5.8	6.2
	8H	5.3	5.5	5.7	5.9	6.3	5.3	5.5	5.7	5.9	6.3
	12H	5.3	5.6	5.7	6.0	6.4	5.3	5.6	5.7	6.0	6.4
8H	4H	4.8	5.1	5.2	5.5	5.9	4.8	5.1	5.2	5.5	5.9
	6H	5.4	5.6	5.8	6.0	6.4	5.4	5.6	5.8	6.0	6.4
	8H	5.5	5.7	6.0	6.1	6.6	5.5	5.7	6.0	6.1	6.6
	12H	5.6	5.7	6.1	6.2	6.7	5.6	5.7	6.1	6.2	6.7
12H	4H	4.8	5.1	5.2	5.5	5.9	4.8	5.1	5.2	5.5	5.9
	6H	5.4	5.6	5.8	6.0	6.5	5.4	5.6	5.8	6.0	6.5
	8H	5.5	5.7	6.0	6.1	6.6	5.5	5.7	6.0	6.1	6.6
ariation of t	he observer	position	for the lum	inaire disti	ences S						
S = 1.0H		+5.8 / -11.9					+5.8 / -11.9				
S = 1.5H		+8.6 / -13.2				+8.6 / -13.2					
S = 2.0H		+10.6 / -13.9					+10.6 / -13.9				
Standard table		BK00					BK00				
Correction Summand		-3.9					-3.9				

Dimensional Drawing

