

ARTILUX spot facede light, Narrow beam angle, 12-cm Dia., RGB, LED1, 500 Lumens, 15W, Milk white

About Product

ARTILUX spot facade light is Mazinoor state of the art design suitable for architectural and outdoor facade lighting applications such as building facades. Aesthetically beautiful design, sturdy structure, specially designed lenses with medium or narrow light distribution, flexibility in light direction adjustment, and high ingress protection (IP66) are among the highlights of this luminaire.




Technical Information



ARTILUX spot facede light, Narrow beam angle, 12-cm Dia., RGB, LED1, 500 Lumens, 15W, Milk white

Photometric Graph



ρ Ceiling		70	70	50	50	30	70	70	50	50	30
ρ Walls		50	30	50	30	30	50	30	50	30	30
P Floor Room Size X Y		20	20	20	20	20	20	20	20	20	20
		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	-9.5	-8.8	-9.2	-8.6	-8.4	-9.5	-8.8	-9.2	-8.6	-8.4
	3H	-9.4	-8.8	-9.1	-8.6	-8.3	-9.4	-8.8	-9.1	-8.6	-8.3
	4H	-9.5	-8.9	-9.2	-8.7	-8.4	-9.5	-8.9	-9.2	-8.7	-8.4
	6H	-9.5	-9.0	-9.2	-8.7	-8.5	-9.5	-9.0	-9.2	-8.7	-8.5
	8H	-9.6	-9.1	-9.2	-8.8	-8.5	-9.6	-9.1	-9.2	-8.8	-8.5
	12H	-9.6	-9.1	-9.3	-8.8	-8.5	-9.6	-9.1	-9.3	-8.8	-8.5
4Н	2H	-9.3	-8.8	-9.0	-8.5	-8.3	-9.3	-8.8	-9.0	-8.5	-8.3
	3H	-9.3	-8.9	-9.0	-8.6	-8.2	-9.3	-8.9	-9.0	-8.6	-8.2
	4H	-9.4	-9.0	-9.0	-8.7	-8.3	-9.4	-9.0	-9.0	-8.7	-8.3
	6H	-9.5	-9.1	-9.1	-8.8	-8.4	-9.5	-9.1	-9.1	-8.8	-8.4
	8H	-9.5	-9.2	-9.1	-8.8	-8.4	-9.5	-9.2	-9.1	-8.8	-8.4
	12H	-9.5	-9.3	-9.1	-8.9	-8.5	-9.5	-9.3	-9.1	-8.9	-8.5
8H	4H	-9.5	-9.2	-9.1	-8.8	-8.4	-9.5	-9.2	-9.1	-8.8	-8.4
	6H	-9.6	-9.4	-9.1	-9.0	-8.5	-9.6	-9.4	-9.1	-9.0	-8.5
	8H	-9.6	-9.5	-9.2	-9.0	-8.6	-9.6	-9.5	-9.2	-9.0	-8.6
	12H	-9.7	-9.5	-9.2	-9.1	-8.6	-9.7	-9.5	-9.2	-9.1	-8.6
12H	4H	-9.5	-9.3	-9.1	-8.9	-8.5	-9.5	-9.3	-9.1	-8.9	-8.5
	6H	-9.6	-9.5	-9.2	-9.0	-8.6	-9.6	-9.5	-9.2	-9.0	-8.6
	8H	-9.7	-9.5	-9.2	-9.1	-8.6	-9.7	-9.5	-9.2	-9.1	-8.6
Variation of	the observer	position	for the lum	inaire dist	ances S						
S = 1.0H		+1.6 / -1.5					+1.6 / -1.5				
S = 1.5H		+3.1 / -4.3					+3.1 / -4.3				
S = 2.0H		+4.7 / -8.6					+4.7 / -8.6				
Standard table		BK01					BK01				
Correction Summand		-22.8					-22.8				

Dimensional Drawing

