

LEDiSUN L decorative LED High-Bay pendant (DOB), with Wide symmetrical light beam angle, 4000K, LED8, 21000 Lumens, 200W, Silver

About Product




Technical Information



LEDiSUN L decorative LED High-Bay pendant (DOB), with Wide symmetrical light beam angle, 4000K, LED8, 21000 Lumens, 200W, Silver

Photometric Graph



p Ceiling		70	70	50	50	30	70	70	50	50	30
p Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room Size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	10.6	11.5	10.8	11.7	11.9	10.6	11.5	10.8	11.7	11.9
	3H	10.8	11.6	11.1	11.9	12.1	10.8	11.6	11.1	11.9	12.1
	4H	10.8	11.6	11.1	11.8	12.1	10.8	11.6	11.1	11.8	12.
	6H	10.9	11.6	11.2	11.9	12.2	10.9	11.6	11.2	11.9	12.3
	8H	10.9	11.6	11.3	11.9	12.2	10.9	11.6	11.3	11.9	12.3
	12H	10.9	11.6	11.3	11.9	12.2	10.9	11.6	11.3	11.9	12.3
4H	2H	10.6	11.3	10.9	11.6	11.9	10.6	11.3	10.9	11.6	11.9
	3H	10.9	11.5	11.2	11.8	12.1	10.9	11.5	11.2	11.8	12.
	4H	11.0	11.5	11.3	11.8	12.2	11.0	11.5	11.3	11.8	12.3
	6H	11.1	11.5	11.5	11.9	12.3	11.1	11.5	11.5	11.9	12.3
	8H	11.2	11.6	11.6	12.0	12.4	11.2	11.6	11.6	12.0	12.4
	12H	11.2	11.6	11.6	12.0	12.4	11.2	11.6	11.6	12.0	12.4
8H	4H	10.9	11.4	11.4	11.7	12.1	10.9	11.4	11.4	11.7	12.3
	6H	11.1	11.5	11.6	11.9	12.3	11.1	11.5	11.6	11.9	12.3
	SH	11.2	11.5	11.7	12.0	12.5	11.2	11.5	11.7	12.0	12.5
	12H	11.3	11.6	11.8	12.1	12.6	11.3	11.6	11.8	12.1	12.0
12H	4H	10.9	11.3	11.3	11.7	12.1	10.9	11.3	11.3	11.7	12.
	6H	11.1	11.4	11.6	11.9	12.3	11.1	11.4	11.6	11.9	12.3
	SH	11.3	11.5	11.8	12.0	12.5	11.3	11.5	11.8	12.0	12.5
Variation of t	he observer	position	for the lum	inaire dist	ances S						
S = 1.0H		+2.0 / -6.8					+2.0 / -6.8				
S = 1.5H		+4.1 / -10.9					+4.1 / -10.9				
S = 2.0H		+6.1 / -12.2					+6.1 / -12.2				
Standard table		BK00					BK00				
Correction Summand		-8.1					-8.1				

Dimensional Drawing

