

LEDiLUX recessed light panel for gypsum false ceiling (60\*60), Satin white diffuser, 6500K, LED2, 4500 Lumens, 29W, White


**About Product** 

**Technical Information** 



## LEDiLUX recessed light panel for gypsum false ceiling (60\*60), Satin white diffuser, 6500K, LED2, 4500 Lumens, 29W, White

## **Photometric Graph**



p Ceiling		70	70	50	50	30	70	70	50	50	30
o Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room Size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	17.5	18.9	17.8	19.1	19.3	16.8	18.2	17.1	18.4	18.
	3H	19.1	20.4	19.5	20.6	20.9	18.4	19.6	18.7	19.9	20.
	4H	19.8	21.0	20.2	21.3	21.6	19.0	20.1	19.3	20.4	20.7
	6H	20.4	21.4	20.7	21.7	22.0	19.5	20.5	19.8	20.8	21.2
	SH	20.5	21.6	20.9	21.9	22.2	19.6	20.7	20.0	21.0	21.3
	12H	20.7	21.7	21.1	22.0	22.3	19.7	20.7	20.1	21.0	21.4
4H	2H	18.1	19.3	18.5	19.6	19.9	17.6	18.8	17.9	19.0	19.3
	3H	20.0	21.0	20.3	21.3	21.6	19.3	20.3	19.7	20.6	21.0
	4H	20.8	21.7	21.2	22.0	22.4	20.1	21.0	20.5	21.3	21.
	6H	21.5	22.2	21.9	22.6	23.0	20.7	21.5	21.1	21.8	22.2
	SH	21.7	22.4	22.1	22.8	23.2	20,9	21.6	21.3	22.0	22.4
	12H	21.9	22.6	22.4	23.0	23.4	21.1	21.7	21.5	22.1	22.0
8H	4H	21.1	21.8	21.5	22.2	22.6	20.5	21.2	20.9	21.6	22.0
	6H	21.9	22.5	22.4	22.9	23.4	21.2	21.8	21.7	22.2	22.
	SH	22.2	22.8	22.7	23.2	23.7	21.5	22.0	22.0	22.5	23.0
	12H	22.5	23.0	23.0	23.4	23.9	21.8	22.2	22.2	22.7	23.2
12H	4H	21.1	21.7	21.5	22.2	22.6	20.5	21.2	21.0	21.6	22.0
	6H	22.0	22.5	22.4	22.9	23.4	21.3	21.8	21.8	22.3	22.8
	8H	22.4	22.8	22.8	23.3	23.8	21.7	22.1	22.2	22.6	23.:
ariation of	the observer	position	for the lum	inalre dista	ances S						
S = 1.0H		+0.1 / -0.1					+0.1 / -0.1				
S = 1.5H		+0.2 / -0.3					+0.2 / -0.4				
S = 2.0H		+0.4 / -0.6					+0.4 / -0.7				
Standard table		BK06					BK06				
Correction Summand		5.0					4.3				

## **Dimensional Drawing**

