

Comfort DIANA LED IP54 recessed Downlight, Low UGR diffuser, white shader, 20cm Dia., 6500K, LED4, 2800 Lumens, 24W, White

**About Product** 




**Technical Information** 



## Comfort DIANA LED IP54 recessed Downlight, Low UGR diffuser, white shader, 20cm Dia., 6500K, LED4, 2800 Lumens, 24W, White

## **Photometric Graph**



ρ Walls ρ Floor Room S χ		50			50	30	70	70	50	50	30	
Room S			30	50	30	30	50	30	50	30	30	
		20	20	20	20	20	20	20	20	20	20	
	Room Size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	8.8	9.7	9.0	9.9	10.1	8.8	9.7	9.0	9.9	10.1	
	3H	9.8	10.6	10.1	10.8	11.1	9.8	10.6	10.1	10.8	11.1	
	4H	9.9	10.6	10.2	10.9	11.2	9.9	10.6	10.2	10.9	11.3	
	6H	9.9	10.6	10.2	10.9	11.2	9.9	10.6	10.2	10.9	11.3	
	8H	9.9	10.5	10.2	10.8	11.1	9.9	10.5	10.2	10.8	11.3	
	12H	9.9	10.5	10.2	10.8	11.1	9.9	10.5	10.2	10.8	11.1	
4Н	2H	9.2	9.9	9.5	10.2	10.4	9.2	9.9	9.5	10.2	10.4	
	3H	10.3	10.9	10.6	11.2	11.5	10.3	10.9	10.6	11.2	11.5	
	4H	10.4	10.9	10.8	11.3	11.6	10.4	10.9	10.8	11.3	11.6	
	6H	10.4	10.9	10.8	11.3	11.6	10.4	10.9	10.8	11.3	11.6	
	8H	10.4	10.9	10.9	11.2	11.6	10.4	10.9	10.9	11.2	11.6	
	12H	10.4	10.8	10.9	11.2	11.6	10.4	10.8	10.9	11.2	11.6	
8H	4H	10.4	10.8	10.8	11.2	11.6	10.4	10.8	10.8	11.2	11.6	
	6H	10.5	10.8	10.9	11.2	11.7	10.5	10.8	10.9	11.2	11.7	
	8H	10.5	10.8	11.0	11.2	11.7	10.5	10.8	11.0	11.2	11.7	
	12H	10.5	10.7	11.0	11.2	11.7	10.5	10.7	11.0	11.2	11.3	
12H	4H	10.4	10.7	10.8	11.1	11.6	10.4	10.7	10.8	11.1	11.6	
	6H	10.4	10.7	10.9	11.2	11.6	10.4	10.7	10.9	11.2	11.6	
	SH	10.5	10.7	11.0	11.2	11.7	10.5	10.7	11.0	11.2	11.7	
Variation of th	e observer	position I	for the lum	inaire dist	ances S							
S = 1.0H		+1.3 / -2.6					+1.3 / -2.6					
S = 1.5H		+3.0 / -3.8					+3.0 / -3.8					
S = 2.0H		+4.7 / -4.5					+4.7 / -4.5					
Standard table		BK01					BK01					
Correction Summand		-8.0					-8.0					

## **Dimensional Drawing**

