

FORTE 1x28 W T5 Fluorescent industrial luminaire with Electronic ballast, specular pre-anodized aluminium reflector, narrow light distribution

About Product




Technical Information



FORTE 1x28 W T5 Fluorescent industrial luminaire with Electronic ballast, specular pre-anodized aluminium reflector, narrow light distribution

Photometric Graph



Ceiling		70	70	50	50	30	70	70	50	50	30
o Walls		50	30	50	30	30	50	30	50	30	30
p Floor		20	20	20	20	20	20	20	20	20	20
Room Size		Viewing direction at right angles					Viewing direction parallel				
X Y		to lamp axis					to lamp axis				
2H	2H	20.8	22.2	21.1	22.4	22.7	19.8	21.1	20.1	21.3	21.
	3H	20.8	22.0	21.1	22.3	22.6	21.3	22.5	21.6	22.8	23.
	4H	20.7	21.9	21.1	22.1	22.4	21.8	23.0	22.2	23.3	23.
	6H	20.6	21.7	21.0	22.0	22.3	22.2	23.2	22.5	23.5	23.
	8H	20.6	21.6	21.0	21.9	22.3	22.2	23.3	22.6	23.6	23.
	12H	20.6	21.5	20.9	21.9	22.2	22.2	23.2	22.6	23.5	23.
4Н	2H	21.3	22.5	21.7	22.7	23.0	20.5	21.6	20.8	21.9	22.
	3H	21.3	22.3	21.7	22.6	23.0	22.3	23.3	22.7	23.6	23.
	4H	21.3	22.1	21.7	22.5	22.8	23.0	23.8	23.4	24.2	24.
	6H	21.2	22.0	21.6	22.3	22.7	23.4	24.1	23.8	24.5	24.
	SH	21.2	21.9	21.6	22.3	22.7	23.5	24.2	23.9	24.6	25.
	12H	21.1	21.8	21.6	22.2	22.6	23.5	24.1	24.0	24.5	25.
8H	4H	21.4	22.0	21.8	22.4	22.9	22.9	23.6	23.3	24.0	24.
	6H	21.3	21.9	21.8	22.3	22.7	23.3	23.9	23.8	24.3	24.
	SH	21.3	21.7	21.7	22.2	22.7	23.5	23.9	23.9	24.4	24.
	12H	21.2	21.6	21.7	22.1	22.6	23.5	23.9	24.0	24.4	24.
12H	4H	21.4	22.0	21.8	22.4	22.8	22.9	23.5	23.3	23.9	24.
	6H	21.3	21.8	21.8	22.2	22.7	23.3	23.8	23.8	24.2	24.
	SH	21.3	21.7	21.7	22.1	22.6	23.4	23.8	23.9	24.3	24.
Variation of	the observer	position	for the lum	inaire dista	ances S						
S = 1.0H		+0.4 / -0.6					+0.2 / -0.2				
S = 1.5H		+1.7 / -2.0				+0.4 / -0.7					
S = 2.0H		+2.8 / -6.5					+1.3 / -2.1				
Standard table		BK01					BK04				
Correction		-0.7					10				
Summand		-0./					1.8				

Dimensional Drawing

