

M104D2400MH

APOLO 400W metal halide industrial high-bay, D2 striped anodized aluminium reflector



About Product




Technical Information



M104D2400MH

APOLO 400W metal halide industrial high-bay, D2 striped anodized aluminium reflector

Photometric Graph



Ceiling		70	70	50	50	30	70	70	50	50	30
Walls		50	30	50	30	30	50	30	50	30	30
Floor		20	20	20	20	20	20	20	20	20	20
Room Size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	26.7	28.1	27.0	28.3	28.6	26.7	28.1	27.0	28.3	28.6
	3H	27.9	29.1	28.2	29.4	29.6	27.9	29.1	28.2	29.4	29.6
	4H	28.1	29.2	28.4	29.5	29.8	28.1	29.2	28.4	29.5	29.8
	6H	28.1	29.2	28.5	29.5	29.8	28.1	29.2	28.5	29.5	29.8
	8H	28.1	29.1	28.5	29.5	29.8	28.1	29.1	28.5	29.5	29.8
	12H	28.1	29.1	28.5	29.4	29.7	28.1	29.1	28.5	29.4	29.7
4H	2H	27.1	28.3	27.5	28.6	28.9	27.1	28.3	27.5	28.6	28.9
	3H	28.4	29.4	28.8	29.7	30.1	28.4	29.4	28.8	29.7	30.1
	4H	28.7	29.6	29.1	29.9	30.3	28.7	29.6	29.1	29.9	30.3
	6H	28.8	29.6	29.2	29.9	30.3	28.8	29.6	29.2	29.9	30.3
	8H	28.8	29.5	29.2	29.9	30.3	28.8	29.5	29.2	29.9	30.3
	12H	28.8	29.4	29.2	29.8	30.3	28.8	29.4	29.2	29.8	30.3
8H	4H	28.8	29.5	29.2	29.9	30.3	28.8	29.5	29.2	29.9	30.3
	6H	28.9	29.5	29.4	29.9	30.4	28.9	29.5	29.4	29.9	30.4
	8H	28.9	29.4	29.4	29.9	30.4	28.9	29.4	29.4	29.9	30.4
	12H	28.9	29.3	29.4	29.8	30.3	28.9	29.3	29.4	29.8	30.3
12H	4H	28.8	29.4	29.2	29.8	30.2	28.8	29.4	29.2	29.8	30.2
	6H	28.9	29.4	29.4	29.9	30.3	28.9	29.4	29.4	29.9	30.3
	8H	28.9	29.4	29.4	29.8	30.3	28.9	29.4	29.4	29.8	30.3
ariation of t	he observer	position	for the lum	inaire dist	ances S						
S = 1.0H		+0.2 / -0.1					+0.2 / -0.1				
S = 1.5H		+0.5 / -0.6				+0.5 / -0.6					
S = 2.0H		+0.9 / -1.3				+0.9 / -1.3					
Standard table		BK03					BK03				
Correction Summand		-2.3					-2.3				

Dimensional Drawing

